

OFFICE OF THE REGULATED MARKET COMMITTEE, MALKANGIRI


Letter No 417 /19

Date 21/08/19

SHORT TENDER CALL NOTICE

Sealed and signed tender paper are invited from the bidder with super scribed on the top of the envelop " SHORT TENDER CALL NOTICE FOR SUPPLY OF Desk top, table, thermal printer, UPS, Laser Jet printer, Dungal (Wi-Fi), Table, Chair etc. for use of e-NAM Mandi. The sealed tender paper should reach to the undersigned on or before dt. 06.09.2019 by 4.00 pm through regd. Post/ speed post only to the address, Secretary RMC, , Malkangiri " and it will be opened on dt. 07.09.2019 at 11.30 A.M. in the office of RMC in presence of bidders / the authorized representatives. The firms are requested to log on the district website www.malkangiri.nic.in for the details terms & conditions and technical specification etc. the undersigned reserves to cancel any or call of the tender without assigning the reason thereof.

BY ORDER OF CHAIRMAN


Secretary RMC
Malkangiri

Memo No 418 /19

Dt. 21/08/19


Copy submitted to the District information Officer, NIC Malkangiri for information. He is requested to upload the entire tender documents including terms and conditions and specification of the products to facilitate for downloading by the intending bidders w.e.f. 22.08.2019 to 06.09.2019. Down loading should not be available after expire of the mention date and time.


Secretary RMC
Malkangiri

OFFICE OF THE REGULATED MARKET COMMITTEE, MALKANGIRI

TERMS AND CONDITIONS

- 1 The undersigned shall have the right to reject all or any of the quotation without assigning any reason thereof.
- 2 The tender received after due date and time will be rejected. The tender paper will be received through regd. Post / speed post/ Courier Service only.
- 3 The bidders are to submit their tender in a separate envelope. The cover should super scribed on the top of the envelop " SHORT TENDER CALL NOTICE FOR SUPPLY OF (product)
- 4 The bidder submit a sum of Rs. 1000/- (Rupees one thousand only) as tender fee (non refundable) and Rs. 5000/- (Rupees five thousand only) as EMD (refundable without any interest) for the unsuccessful tender. The tender fee EMD should be submit in shape of Demand draft drawn in favour of Secretary RMC and payable at Malkangiri. The SSI units and EP & M holders are exempted for EMD as per recent circular of the Directorate of Export promotion & Marketing, Odisha subject to production of valid registration certificate from MSME Deptt.
- 5 The items should be supplied according to the quality and specification mentioned in the quotation.
- 6 Deviation of quality results in returns of items even after supply and recovery of payment of cost.
- 7 The articles should be delivered to the RMC, Malkangiri.
- 8 The supply should be complete within a week from the date of placement of order.
- 9 The rates should be valid for one year.
- 10 All the items will be delivered at the office of the undersigned


Secretary RMC
Malkangiri

OFFICE OF THE REGULATED MARKET COMMITTEE, MALKANGIRI**PARTICULARS OF EQUIPMENT**

Following items are required by the undersigned

Sl. No.	Particulars	annexure
1	Desktop	A
2	Table	B
3	Thermal printer	C
4	UPS	D
5	Laser jet printer	E
6	Dangle (wi-fi)	F
7	Table	G
8	Chair	H

REGULATED MARKET COMMITTEE, MALKANGIRI

ANNEXURE- A (Desktop)

PC-01-Desktop

Make & Model	
Processor	Intel Core i5-4570, 3.2 GHz, 6 MB Cache or its higher version
Chipset	Intel Q8 series
Motherboard	Standard OEM
RAM	4 GB 1600 MHz DDR3 RAM with 32 GB Expandability
Hard drive	500 GB 7200 rpm or higher
Audio	
NIC	10/100/1000 on board integrated Network Port with remote booting facility remote system installation, remote wake up, TPM enabled 1.2 chip using any standard management software
Display Monitor	47 cm or larger (18.5 inch or larger) TFT/LED Digital Colour Monitor TCO-05 certified.
Keyboard	104 keys. USB Keyboard
Mouse	Optical with USB interface
Ports	6 USB Ports or more (at least 2 USB with 3.0), 1 Display port/VGA port, audio ports for microphone headphone in front
Form Factor	Tower/Mini Tower
Power Supply	
Certifications	Windows 8 OS certification.
Operating System	Windows 8 Professional as specified, with Media and Documentation and Certificate of Authenticity
Preloaded Software	Microsoft Office/ Open Office, Adobe PDF, Microsoft Security Essentials
Accessories	8X or better DVD ROM Drive
Warranty	3 Years Onsite Warranty

(4)

REGULATED MARKET COMMITTEE, MALKANGIRI

ANNEXURE- B (TABLE)

(5)

REGULATED MARKET COMMITTEE, MALKANGIRI

ANNEXURE- C (Thermal printer)

Thermal 3" Printer

Make & Model	
Print	
Paper Dimensions	Width: 79.5 ± 0.5 mm (3.13" ± 0.02") Diameter: 83 mm (3.27") maximum
Paper Thickness	0.06 to 0.07 mm (0.002" to 0.003")
Print Speed	NORMAL: 150 mm/s (5.91"/s), Approx 40.0 Ips (3.75 mm [0.15"] feed) PAGE MODE PRINTING: 150 mm/s (5.91"/s) BIT-IMAGE PRINTING: 150 mm/s (5.91"/s) RASTER BIT-IMAGE PRINTING: 150 mm/s (5.91"/s) LADDER BAR CODE, 2 DIMENSIONAL PRINTING: 99 mm/s (3.90"/s)
Interfaces	Serial, Parallel, USB, Ethernet
Print Fonts	12 x 24 / 9 x 17 / 9 x 24 mm (including 2-dot spacing horizontally)
Characters Set	95 Alphanumerical, 1 x International, 128 x 1 Extended Graphic Thai (128 x 3) & Vietnam (128 x 2) Characters
Paper Type	Thermal roll paper
Power	
Power Consumption	Approx. 1.4 A (Mean)
Power Supply Option	PS-180 (included)
Power Supply	24VCD ± 7%
General	
Weight	Approx. 1.7 kg

Dimensions	144 (W) × 189 (D) × 145 (H) mm 5.67" (W) × 7.44" (D) × 5.71" (H)
Reliability	
Reliability MCBF	52 million lines Auto cutter 1.5 million cuts
Reliability MTBF	360,000 hours

(6)

REGULATED MARKET COMMITTEE, MALKANGIRI

ANNEXURE- D (UPS)

UPS-02- 1KVA On-Line UPS

Make& Model	
Capacity	1.5 KVA / 1200Watts
Technology	Advanced DSP based True Online UPS with double conversion technology
Self Test	
Input	
Voltage Range	160 to 300 VAC

Frequency Range	50 Hz +/- 5%
Phase	1-phase, 3 wire
Power Factor	>0.99
Output	
Voltage	220VAC / 230VAC / 240VAC +/- 1%, 1phase
Voltage Regulation	
Frequency	50 to 60 Hz +/- 3 Auto Sense
Output Waveform	Pure sin wave
Crest Factor	3:1 max.
Efficiency AC - AC	Min 85% (online mode)
Power Factor	0.8 pf
Overload capacity	125% for 10 min., 150% for 1 min.
Battery	
Battery Capacity	5400 VAH OR ABOVE
Rack	Powder coated battery rack/Stand to be provided
Battery Type	Sealed Maintenance Free Batteries (Exide Power safe / Numeric / Amaron)
Charger	Built-in solid state float-cum-boost charger with automatic boost
General	
Operating temperature	0 to 50 Deg. C
Line Mode to Battery mode transfer time	0 ms
Cold start	
Display & User Friendly front panel	LCD display for status/fault information
Indications	
Audible Alarm	
Protection	All critical source and sensitive loads should have protection from transients, Advanced Electronic Protection for device safety for rectifier and Inverter, Built-in Overload protection, from short Circuits
Auto restart	
Bypass	
Standard Interface	
Certification	
Cabling and Connectors	
Warranty	Comprehensive 3 years Onsite warranty for UPS & Batteries including spares.

REGULATED MARKET COMMITTEE, MALKANGIRI

ANNEXURE- F (LED TV)**Professional Displays**

Picture/Display	<ul style="list-style-type: none"> • Diagonal screen size: 31.5 inch / 80 cm • Panel resolution: 1920 x 1080p • Optimum resolution: 1920 x 1080 @ 60 Hz • Brightness: 350 cd/m² • Contrast ratio (typical): 1400:1 • Dynamic contrast ratio: 500,000:1 • Response time (typical): 8 ms • Aspect ratio: 16:9 • Viewing Angle (H / V): 178 / 178 degree • Pixel pitch: 0.36375 x 0.36375 mm • Display colours: 16.7 Million • DICOM: Clinical D-image
Supported Display Resolution	<ul style="list-style-type: none"> • Computer formats Resolution Refresh rate 640 x 480 60, 67, 72, 75 Hz 800 x 600 56, 60, 72, 75 Hz 1024 x 768 60 Hz 1280 x 768 60 Hz 1280 x 800 60 Hz 1360 x 768 60 Hz 1366 x 768 60 Hz 1440 x 900 60 Hz 1600 x 1200 60 Hz 1920 x 1080 60 Hz 1920 x 1200 60 Hz • Video formats Resolution Refresh rate 480i 60 Hz 480p 60 Hz 576p 50 Hz 576i 50 Hz 720p 50, 60 Hz 1080i 50, 60 Hz 1080p 50, 60 Hz
Connectivity	<ul style="list-style-type: none"> • Video input: DVI-D, HDMI, Component (RCA), Composite (RCA), VGA (Analogue D-Sub) • Audio input: 3.5-mm jack, Audio Left/Right (RCA) • Audio output: Audio Left/Right (RCA), 3.5 mm jack • External control: RJ45, RS232C (In/out) 2.5 mm jack, IR (in/out) 3.5 mm jack • Other connections: USB
Convenience	<ul style="list-style-type: none"> • Memory: Internal memory access, 8 GB eMMC • Screen-saving functions: Pixel Shift • Energy-saving functions: Smart Power • Tiled Matrix: Up to 15 x 15 • Start-up: Switch on delay, Switch on status, Wake up on LAN • Start-up window: enable/disable Philips logo • Keyboard control: Lockable, Hidden • Network controllable: RS232, RJ45, One Wire (HDMI-CEC)

Dimensions	<ul style="list-style-type: none"> • Signal Loop Through: RS232, IR Loop through • Bezel width: 11.9 (TLR)/17.2 (B) mm • Set dimensions (W x H x D): 726.5 x 425.4 x 63.6 mm • Set dimensions in inch (W x H x D): 28.6 x 16.75 x 2.5 inch • VESA Mount: 100 x 100 mm, 200 x 200 mm, M4 • Product weight: 5.20 kg • Product weight (lb): 14.74
Operating conditions	<ul style="list-style-type: none"> • Temperature range (operation): 5 ~ 40 °C • Temperature range (storage): -20 ~ 60 °C • Relative humidity: 20 ~ 80 % • MTBF: 50,000 hour(s)
Power	<ul style="list-style-type: none"> • Consumption (On mode): 32 W (EnergyStar 6.0 test method) • Mains power: 100 ~ 240 VAC • Standby power consumption: <0.5 W
Sound	<ul style="list-style-type: none"> • Built-in speakers: 2 x 10 W RMS
Multimedia Applications	<ul style="list-style-type: none"> • USB Playback Video: 3G2, 3GP, ASF, ASX, AVI, DAT, DivX, F4V, FLV, M2TS, M4V, MK3D, MKV, MOV, MP4, MPE, MPEG, MPG, MTS, QT, TRP, TS, TTS, VOB, WEBM, WMV, Xvid • USB Playback Picture: BMP, GIF, JPEG, JPG • USB Playback Audio: AAC, AC3, AIF, AIFF, AMR, EC3, M4A, MP3, OGA, OGG, WAV, WMA
Accessories	<ul style="list-style-type: none"> • Included accessories: AC Power Cord, RS232 cable, VGA cable, Remote Control, Batteries for remote control, User manual on CD-ROM, Quick start guide
Miscellaneous	<ul style="list-style-type: none"> • Warranty: 3-year warranty • On-Screen Display Languages: English, French, German, Italian, Polish, Turkish, Russian, Simplified Chinese, Spanish, Traditional Chinese • Regulatory approvals: BSMI, CB, CCC, CE, CECP, C-Tick, EPA, GOST, UL/cUL

(9)

REGULATED MARKET COMMITTEE, MALKANGIRI

ANNEXURE- f (Dongle)

ANNEXURE- G (Table)

ANNEXURE- H (Table)